



Start with a better finish!

RSA BLING COARSE (LB, MB, UDB)

TECHNICAL DATA SHEET

PRECAUTIONS AND LIMITATIONS

This product should not be applied in windy conditions and in temperatures below 5°C (temperature must be climbing on application and should not fall below 5°C within eight hours of application) or above 35°C. Protect from freezing and temperatures below 5°C for 48 hours after application. Protect from rain for up to 48 hours after application.

When applied, this product cannot be expected to hide imperfections, correct poor quality substrate installations or overcome preparation / workmanship deficiencies.

This product does not have the ability to bridge structural cracks other than micro / hairline cracks.

Batch-to-batch colour variations may occur due to the incorporation of natural sand in the product.

Substrates and previous RSA coatings must contain less than 15% Wood Moisture Equivalent (WME) prior to the application of RSA Bling Coarse.

PRODUCT DESCRIPTION

Render Systems Australia Bling Coarse is an acrylic based, high quality finish which does not require over-coating with a paint. It is a unique formulation containing natural quartz stone which provides the surface with an attractive shimmer and sparkle when exposed to light. Bling Coarse consists of high quality washed and graded aggregates, polymers, acrylic binders, as well as water resisting and hydrophobic agents. Bling Coarse is available in Light Base (LB), Mid Base (MB) and Ultra Deep Base (UDB).

FEATURES AND BENEFITS

- ✓ Offers excellent water resistance without the need for paint
- ✓ Provides a shimmering sparkle effect when exposed to light
- ✓ Available in a wide range of bases for tinting requirements
- ✓ Provides a decorative top coat with high flexibility
- ✓ Offers excellent wet edge properties to assist the plasterer in a seamless finish
- ✓ Provides excellent depth and coverage due to natural stone size
- ✓ Results in an attractive, unique finish suitable for any broad wall or feature area

SUITABLE SUBSTRATES

When applied in accordance with the most recent Application Instructions, Bling Coarse is suitable for use over correctly prepared substrates including:

- ✓ Acrylic and cement based renders
- ✓ Slab edge, off-form and tilt panel concrete
- ✓ Painted surfaces
- ✓ Gyprock plasterboard
- ✓ Fibre cement sheeting

APPLICATION GUIDELINES

1. RSA Multiprime (tinted to finish colour) must be applied prior to Bling Coarse.
2. Bling Coarse is applied by steel trowel in thicknesses from 1 - 2mm per coat and finished using a plastic float. As a general rule, the size of the incorporated aggregate will determine the depth of an individual coat.

TINTING AND OVERCOATING

A minimum of one coat of RSA Cleanskin is an optional recommendation for further protection of the system - particularly where ease of cleaning and maintenance is preferred. Colour Selections must achieve a LRV > than 40% when coating over all lightweight claddings for warranty purposes. It is the applicators responsibility to request and sign off on a sample of each product tinted to the required colour prior to application. Please refer to the RSA Colour and Tinting policy and procedure document.



RSA BLING COARSE

TECHNICAL DATA SHEET

PLEASE NOTE

The information given in this Technical Data Sheet is based on current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexpert or negligent application or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project - since the owner or their contractor (and not River Sands) is responsible for procedures relating to the application of the product.

FURTHER INFORMATION

For further information consult the Material Safety Data Sheet (MSDS) and read the product label carefully before use.

MSDS documents are available by phoning 1800 077 744.

TECHNICAL AND APPLICATION DATA

Colour Bases	Light Base (LB), Mid Base (MB) and Ultra Deep Base (UDB)
Coverage	One 15 litre pail applied at 1mm thick will cover approximately 10m ²
Toxicity	Lead free and dry film is non-toxic and conforms with AS 1647
Application	Hawk and Trowel
Drying Time	Please refer to the Application Guidelines for relevant substrate & product
Over Coating	Please refer to the Application Guidelines for relevant substrate & product
Wet Film Thickness	1078 microns
Dry Film Thickness	647 microns
Shelf Life	Two years when stored in a cool, dry environment
Coats	1 - 2 coats
Flammability	Non-flammable
Clean Up	Protect all areas not to be coated and clean with potable water. Use CCS Citric Cleaner immediately after application to remove product from surrounding areas (e.g. window frames).

TRANSPORT AND STORAGE

Packaging Type	15 litre plastic pails
Pails Per Pallet	48
Weight	23.5kg
Dangerous Goods	n/a

WARRANTY

Render Systems Australia (RSA) offers a 7 Year Product Warranty provided:

1. All substrates are installed in accordance with manufacturers specifications, Australian Standards and Good Trade Practices.
2. All products and processes as detailed above are applied by an RSA preferred contractor and in accordance with RSA Technical Data Sheets, Specifications, Application Guidelines and Good Trade Practices.
3. Guidelines Only - always refer to RSA System Specifications and Application Guidelines.

RSA strongly recommend viewing a physical product sample prior to selection of finish and colour.



For more information call Head Office: **07 3412 8111** Toll Free: **1800 077 744**
www.renderssystemsaustralia.com.au