



Start with a better finish!

RSA MASONRY RENDER (MR60, MR120 & MR180)

TECHNICAL DATA SHEET

PRECAUTIONS AND LIMITATIONS

This product should not be applied in windy conditions and in temperatures below 5°C (temperature must be climbing on application and should not fall below 5°C within eight hours of application) or above 35°C. Protect from freezing and temperatures below 5°C for 48 hours after application. Protect from rain for up to 48 hours after application.

When applied, this product cannot be expected to hide imperfections, correct poor quality substrate installations or overcome preparation / workmanship deficiencies.

Batch-to-batch colour variations may occur due to the incorporation of natural sand in the product.

Substrates and previous RSA coatings must contain less than 15% Wood Moisture Equivalent (WME) prior to the application of RSA Masonry Render.

PRODUCT DESCRIPTION

Render Systems Australia Masonry Render is a pre-bonded (10% wet bond equivalent), polymer modified, cement based render that only requires the addition of potable water.

Masonry Render is available in three different set times – MR 60 (60 minute set time), MR 120 (120 minute set time) and MR180 (180 minutes set time).

FEATURES AND BENEFITS

- ✓ Suitable for machine or hand application
- ✓ Provides a non 'tacky' formulation for easier application
- ✓ Available in three set times to suit differing on-site conditions
- ✓ Provides an extended 'hang time' for greater productivity and high early hardness
- ✓ Has great 'straightening qualities' and offers tear resistant screedability
- ✓ Possesses excellent 'come back' qualities for easy floating and finishing

SUITABLE SUBSTRATES

When applied in accordance with the most recent Application Instructions, Masonry Render is suitable for use over correctly prepared substrates including:

- ✓ Clay Bricks
- ✓ Off-form Concrete
- ✓ Concrete Blocks
- ✓ Concrete Slab Edges

When applying RSA products over masonry blocks or clay bricks it is the applicators responsibility to check for variances and irregularities of density and porosity of the substrate before application. Masonry blocks and clay bricks can vary significantly and may affect adhesion of RSA products in some circumstances. It is the applicators responsibility to check with the substrate manufacturer for suitability of a rendered finish if variations of colour, density and porosity are present.



RSA MASONRY RENDER

TECHNICAL DATA SHEET

PLEASE NOTE

The information given in this Technical Data Sheet is based on current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.

To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexpert or negligent application or ordinary wear and tear.

Service or advice given by our staff should not amount to responsibility for the project – since the owner or their contractor (and not River Sands) is responsible for procedures relating to the application of the product.

FURTHER INFORMATION

For further information consult the Material Safety Data Sheet (MSDS) and read the product label carefully before use.

MSDS documents are available by phoning 1800 077 744.

TECHNICAL AND APPLICATION DATA

| | |
|------------------|---|
| Spread Rate | One 20kg bag at 4mm thickness will cover approx 2m ² |
| Toxicity | Non-toxic (dust masks should be worn when mixing product) |
| Application | Steel trowel or render pump |
| Dry Time | Please refer to the Application Guidelines for relevant substrate & product |
| Abrasion | Excellent resistance after 72 hours or when top coated |
| Water Resistance | Excellent resistance when top coated |
| Shelf Life | One year when stored in a cool, dry environment |
| Colour | Off white in appearance |
| Curing | 24 hours per 1mm of render thickness under standard conditions |
| Clean up | Protect all areas not to be coated and clean with potable water |

TRANSPORT AND STORAGE

| | |
|-----------------|-----------------|
| Packaging Type | 20kg paper bags |
| Bags Per Pallet | 48 |
| Dangerous Goods | n/a |

WARRANTY

Render Systems Australia (RSA) offers a 7 Year Product Warranty provided:

1. All substrates are installed in accordance with manufacturers specifications, Australian Standards and Good Trade Practices.
2. All products and processes as detailed above are applied by an RSA preferred contractor and in accordance with RSA Technical Data Sheets, Specifications, Application Guidelines and Good Trade Practices.
3. Guidelines Only – always refer to RSA System Specifications and Application Guidelines.

RSA strongly recommend viewing a physical product sample prior to selection of finish and colour.



For more information call Head Office: **07 3412 8111** Toll Free: **1800 077 744**
www.renderssystemsaustralia.com.au