

PRODUCT DESCRIPTION

Render Systems Australia Sanvito Textureit is a fine profile, granular coating. A range of textured effects can be achieved using selected roller covers, paint mitt, brush or by subsequent trowelling over the rolled surface. RSA Sanvito Textureit can be tinted and will provide an attractive finish on correctly prepared residential & commercial, exterior & interior wall surfaces.

FEATURES AND BENEFITS

- Excellent water resistance
- Excellent vapour permeability
- Excellent durability
- Strong adhesion
- Low maintenance
- Easy to apply
- Water based, easy & safe clean up
- Tintable

TYPICAL USES

RSA Sanvito Textureit is suitable for one or two coat applications over the below substrates.

SUITABLE SUBSTRATES

When applied in accordance with the most recent RSA written information, RSA Sanvito Textureit is suitable for use over a range of correctly prepared substrates including:

- Brick and block
- Autoclaved Aerated Concrete (AAC)
- Rendered Concrete blocks
- Fibre Cement Sheetting
- Rendered Expanded Polystyrene (EPS)
- Concrete tilt panels
- Cement Render
- Rendered Clay Bricks

Note: RSA Sanvito Textureit may be applied to these correctly prepared substrates as part of a system combined with other RSA products & specifications. Refer to substrate specific application guidelines for further information.

THEORETICAL COVERAGE

Usual coverage per 15 litre is approximately 15-18m².

Note: The theoretical coverage is based on a true flat substrate that has no recesses or voids with minimum suction (porosity) and depends on application techniques.

PREPARATION

Ensure all surfaces to be coated are sound, clean, dry, free from dust, oil, release agents, loose material, efflorescence and/or other contaminants. Cover and protect all surfaces not to be coated.

Masking

For all surfaces not to be coated (windows, doors, roofs, finished floors) we recommend masking, covering or otherwise protecting the surface prior to any application.

MIXING

RSA Sanvito Textureit does not require thinning or dilution. Mix thoroughly with a broad, flat stirrer, using an upward lifting action, or use a power mixer. Power mixing is recommended as this will enhance the workability and give the best coverage.

APPLICATION GUIDE

- If applying RSA Sanvito with a suitable texture roller. Ensure the roller is loaded generously and apply in downward strips of 500-750mm in length.
- Once five or six strips have been applied to the surface, roll across the surface to make a uniform and even application.
- Only finish the entire job in one direction for an even uniform texture.
- Repeat the above steps, only re-rolling 70-100mm into the previously coated area.
- Apply rapidly and without interruption, laying off from the edge to avoid any imperfections in the texture.
- It is recommended that any touch up be made when the area is dry. Ensure enough material for whole job.
- If not sufficient material, feather the edge and allow texture to dry, then tie in with newly available material.
- RSA Sanvito Textureit should not be over extended or spread too far; follow recommended coverage rates.

Important Notes

- Care should be taken to avoid getting RSA Sanvito Textureit on windows and adjacent surfaces not to be coated as removal once dry is difficult.
- Do not apply RSA Sanvito Textureit if showers or wet weather is anticipated within 5 hours of completion of application, longer in damp, cold +/- or humid conditions.
- Avoid application in full sun, on hot surfaces or in hot windy conditions.
- Do not apply if Relative Humidity is above 85% or temperature is within 3°C of Dew Point. ascertain this.

- Application should only take place when ambient temperatures are between 10°C and 32°C.
- Surface temperature must be above 10°C for drying to occur.
- Protect newly coated surfaces from damage until the completion of the project, i.e. completed work must be protected from rain, frost, dew and severe weather conditions for at least 48 hours or until completely dry.
- Substrates must have a residual moisture content <10%. Use of a moisture meter is highly recommended to ascertain this.
- RSA Sanvito Textureit can be over coated with RSA Rapidshield Matt for best colour accuracy, to improve durability and to reduce dirt pickup.

LIMITATIONS

The product will not remedy poor quality substrate installations. RSA Sanvito Textureit is not a substitute for good solid plastering trade practices. It is the plasterer's responsibility to assess each project to determine 'best practice'.

CLEAN UP

Clean all equipment immediately with water.

SHELF LIFE

Maximum two (2) years from date of manufacture when stored correctly.

TRANSPORT & STORAGE

Do not stack pails more than three (3) high during transportation. Pails must be transported upright. Store in a cool place, upright, out of direct sunlight and above 4°C.

PRODUCT SAFETY

Refer to Safety Data Sheets

TECHNICAL AND APPLICATION DATA	
APPEARANCE	Off white textured viscous
ODOUR	liquid
APPLICATION METHOD	Low
THEORETICAL COVERAGE	Roller, mitt, trowel, brush
WET FILM THICKNESS	15-18m ² /15 litre pail
DRY TIME (25°C & 50% RH)	Product grain size Tack Free 2-3 Hours (depending on climatic conditions). Coatings reach full cure over weeks/months.
OVERCOAT	After 24 Hours
NO. OF COATS	1-2 coats usually
GLOSS LEVEL	Matt Textured

DISCLAIMER: The information relating to the application of the above products is given in good faith based on our current knowledge and experience of the product when properly stored, handled and applied. We for any purpose other than the stated uses. To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no liability for loss or injury caused by improper use, incompetent preparation, inexperienced or negligent application, or ordinary wear and tear.

All information is correct at the time of printing, however due to our policy of continuing product improvement, we reserve the right to change specifications and literature without written notice. It is the responsibility of those using this information to ensure that it is correct and up to date prior to applying or specifying any of the above mentioned products.