



RSA MASONRY RENDER COARSE – GREY

Technical Data Sheet

PRODUCT DESCRIPTION

Render Systems Australia Masonry Render Coarse Grey is a pre-bonded (10% wet bond equivalent),

polymer modified, cement based render that only requires the addition of potable water.

Due to its coarse grain finish, Masonry Render Coarse Grey is ideal for masking common substrate irregularities.

FEATURES AND BENEFITS

- Offers greater sag resistance for applications requiring a thickness greater than 4mm
- Can be applied as a full render coating in one or two coats at 7-10mm thick and 'screeded flat'
- Offers excellent screed-ability
- Improved formula for easier floating and finishing
- Provides greater productivity and high early strength gains
- Offers an efficient initial set time which can be 'brought back'
- Is an ideal match for RSA Flexirender

SUITABLE SUBSTRATES

When applied in accordance with the most recent Application Instructions, Masonry Render Coarse Grey is suitable for use over correctly prepared substrates including:

- Clay Bricks
- Off Form Concrete
- Concrete Blocks
- Concrete Slab edges

When applying RSA products over masonry blocks or clay bricks it is the applicators responsibility to check for variances and irregularities of density and porosity of the substrate before application. Masonry blocks and clay bricks can vary significantly and may affect adhesion of RSA products in some circumstances. It is the applicators responsibility to check with the substrate manufacturer for suitability of a rendered finish if variations of colour, density and porosity are present.

TECHNICAL AND APPLICATION DATA

| | |
|------------------|---|
| Spread Rate | One 20kg bag at 4mm thickness will cover approx 2m ² |
| Toxicity | Non-toxic (dust masks should be worn when mixing product) |
| Application | Steel trowel |
| Dry Time | Please refer to the Application Guidelines for relevant substrate & product |
| Abrasion | Excellent resistance after 72 hours or when top coated |
| Water Resistance | Excellent resistance when top coated |
| Shelf Life | One year when stored in a cool, dry environment |
| Colour | Grey in appearance |
| Curing | 24 hours per 1mm of render thickness under standard conditions |
| Clean Up | Protect all areas not to be coated and clean with potable water |

TRANSPORT AND STORAGE

| | |
|-----------------|-----------------|
| Packaging Type | 20kg paper bags |
| Bags per Pallet | 48 |
| Dangerous Goods | n/a |

PRECAUTIONS AND LIMITATIONS

This product should not be applied in windy conditions and in temperatures below 5°C (temperature must be climbing on application and should not fall below 5°C within eight hours of application) or above 35°C. Protect from freezing and temperatures below 5°C for 48 hours after application. Protect from rain for up to 48 hours after application.

When applied, this product cannot be expected to hide imperfections, correct poor quality substrate installations or overcome preparation / workmanship deficiencies.

Substrates and previous RSA coatings must contain less than 15% Wood Moisture Equivalent (WME) prior to the application of RSA EP Render.



RSA MASONRY RENDER COARSE – GREY

Technical Data Sheet

WARRANTY

Render Systems Australia (RSA) offers a 7 Year Product Warranty provided:

- 1 All substrates are installed in accordance with manufacturers specifications, Australian Standards and Good Trade Practices.
- 2 All products and processes as detailed above are applied by an RSA preferred contractor and in accordance with RSA Technical Data Sheets, Specifications, Application Guidelines and Good Trade Practices.
- 3 Guidelines Only – always refer to RSA System Specifications and Application Guidelines.

FURTHER INFORMATION

Consult the Safety Data Sheet and read the product label before use. SDS are downloadable via www.renderystems.com.au or call 1800 077 744.

DISCLAIMER: The information relating to the application of the above products is given in good faith based on our current knowledge and experience of the product when properly stored, handled and applied. We cannot guarantee the product will be suitable, effective or safe when used for any purpose other than the stated uses. To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no liability for loss or injury caused by improper use, incompetent preparation, inexpert or negligent application, or ordinary wear and tear.

All information is correct at the time of printing, however due to our policy of continuing product improvement, we reserve the right to change specifications and literature without written notice. It is the responsibility of those using this information to ensure that it is correct and up to date prior to applying or specifying any of the above mentioned products.



Manufactured under a Quality Management System certified to ISO 9001:2015

Render Systems Australia is a division of River Sands Pty Ltd
Further information call 1800 077 744 or email info@renderystems.com.au
www.renderystems.com.au