

RSA Masonry Renders

are available in either an off-white or grey cement base, can be applied in a single coat and are suitable for use all year round. Choose a set time to suit on-site conditions.

RSA Masonry Render – setting time

RSA MR 60, Grey MR 75 and MR 120 renders are pre-bonded (10% wet bond equivalent), polymer modified, cement based renders that only require the addition of potable water.

Available in either an off-white or grey cement base with a choice of setting times.

MR 60 – quicker set time

Grey MR 75 – medium set time

MR 120 – longer set time.


Features and Benefits

- Suitable for machine or hand application
- Provides a non 'tacky' formulation for easier application
- Available in three set times to suit differing on-site conditions
- Provides an extended 'hang time' for greater productivity and high early hardness
- Has great 'straightening qualities' and offers tear resistant screedability
- Possesses excellent 'come back' qualities for easy floating and finishing
- Pre-mixed – simply add water

Suitable Substrates

When applied in accordance with the most recent application instructions, Masonry Render is suitable for use over correctly prepared substrates including:

- Clay bricks
- Off-form concrete
- Concrete blocks
- Concrete slab edges



RSA MR 75 – Grey

[Download TDS](#)

[Download SDS](#)



RSA MR 60 – Off-white

[Download TDS](#)

[Download SDS](#)



RSA MR 120 – Off-white

[Download TDS](#)

[Download SDS](#)